

## E300 80mm Mini Portable Thermal Receipt Printer



### Products Features:

- Business style design, more fashion
- Support 1D, 2D bar code printing
- While compatible with Windows, Linux, Android and IOS systems
- With 2500mAh rechargeable lithium polymer battery, super battery lasting time, with smart power saving and power consumption control functions, to ensure longer print time
- Support USB/USB+Bluetooth/USB+WIFI/USB+Bluetooth+WIFI/COM(customization)
- Special power remaining indicator light, to control the printer power at any time
- Support sound and light reminder when lack of paper or printing abnormal
- Anti fall of 1.5M cement floor

### Application:

Warehousing, transportation, logistics, supermarket, tobacco, hydro power reading, mobile government affairs, mobile police, postal and other industries

### Parameters:

Item		Parameter
Print parameter	Printing Method	Thermal Line
	Effective Printing Width	72mm
	Resolution	576 dots/line (8dots/mm, 203dpi)
	Printing Speed	90mm/S
	Interface	USB/USB+Bluetooth/USB+Wi-Fi/USB+Bluetooth+WIFI/COM(customization)

	Line spacing	3.75mm (Can adjust line spacing by command)
	Line No.	Font A:48 character /Line Font B:64 character/Line
	Character Size	ANK character, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots)
Bar code character	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/ThaiVietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Bar code	1D.Bar code: UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/CODABAR/CODE93/CODE128 2D.Bar code: QRCODE
Graphics printing	Graphics printing	Supports bitmap download and print
Power saving Mode	Smart power saving	Support
	Variable speed printing	Support
	Consumption	Support
	Dormancy	Support
Dection	Sensor	Lack of paper detection
Indicator	Power Display	Support
	Charge Indicator	Support
	Lack of paper	Support
	Beep	Lack of paper,printing abnormal alarm
Paper	Type	Thermal
	Width	79.5±0.5mm
	thickness	≤0.12mm
	Diameter	≤45mm
	Feed	Easy (Clamshell feed)
Print commands	Commands	ESC/POS
Power	Type	Rechargeable Lithium polymer battery
	Capacity	2500mAh/7.4V.
	Charger	9.0V/1A
Buffer	Input	4KB
	NV Flash	40KB
Physical	Weight	285G

features	Dimension	114*103*50(MM)
Environment	Operating	Temp: 5 ~ 45℃ , Humidity: 10 ~ 80%
	Storage	Temp: -10 ~ 50℃ , Humidity: 10 ~ 90% (No Dew)
Reliability	Print head life	50KM (Printing Density≤12.5)
Software	Driver	Android,IOS,Linux,,Windows