


## E803 Thermal Receipt Printer



### Product description:

E803 is a newly designed thermal receipt printer with high reliability and high performance and cost effectiveness. 250mm/s high speed printing, greatly improve printing efficiency; Rich interface selection including USB, Serial, LAN, Bluetooth, WIFI; Real-time printing monitoring function, to avoid losing any bills with great extent, creating a enjoyable and extraordinary printing experience.

### Product performance:

- 250mm/s high speed printing;
- Support wall hanging function, meet the special environment printing;
- Support printer monitoring function, to avoid losing bills;
- Using 100M Ethernet card, Printing more fast and fluently.
- Re-printing after network disconnection, to avoid losing bills;
- Support LOGO Graphical download and print;
- Support 1D, 2D bar code printing;
- Support order come remind and error alarm;
- Support Multi language printing;
- Rich Interface: USB, Serial, Internet, Bluetooth, WIFI, etc. (Interface combination, pls contact manufacture to confirm)
- Support Windows, Linux, Android and IOS system;

### Application:

Shopping malls, restaurants, stores, warehousing, taxation, banking, medical, postal

### Printer Parameters:

Item	Parameters	
Print parameters	Printing Method	Thermal Line
	Printing width	72mm
	Resolution	576 Dots/Line or 512 Dots/Line (8dots/mm, 203dpi)
	Print speed	250mm/Second(MAX)
	Interface	USB,Serial,Internet,Bluetooth,WIFI(Interface combination, pls contact manufacture to confirm)
	Line Spacing	3.75mm (Can adjust line spacing by command)
	Line No.	FontA-48Lines/FontB-64Lines/Simple,traditional Chinese-24lines
	Character	standard GB18030 simplified / BIG5 traditional Chinese Fonts(Japanese and Korean optional)
	Character Size	ANK character: Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) Simplified/Traditional Chinese: 3.0×3.0mm(24×24 dots)
Bar code Character	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/ThaiVietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Bar code	1Dbarcode:UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128 2D barcode: QRCODE
Graphics printing	Graphics printing	Supports bitmap download and print
Paper	Type	Thermal
	Width	79.5±0.5mm
	Diameter	≤80mm
	Feed method	Easy feed(Clameshell feed)
Print commands	Commands	ESC/POS
Power	Power Adaptor	Input: AC 100V-240V,50-60Hz Output: DC 24V/1.5A
	Cash Drawer Output	DC 24V/1A
Buffer	NV Flash	256K bytes
physical characteristics	Weight	0.9KG
	Dimension	185*133*133(MM)
environment	Working	Temp: 5 ~ 45℃, Humidity: 10 ~ 80%
	Storage	Temp: -10 ~ 50℃, Humidity: 10 ~ 90% (No dew)
Reliability parameter	Print Head Life	100KM (print density≤12.5)
	Cutter Life	1000,000times
Software	Driver	Android,IOS,Linux,Windows