

H200 Mini Portable Thermal Receipt Printer



Product description:

HOP-H200 is a newly designed mobile receipt printer with high-performance. Smooth modeling with ergonomic design and excellent grip for easy hand-taking. Support USB fast charging; Support printer working and charging at the same time, greatly improve the efficiency of the printer; Large capacity polymer lithium-ion battery to ensure a long printing time; Simple and practical human-printer interaction promote for the real perfect practical using of the printer.

Products Features:

- Flowing and graceful model with ergonomic design and excellent grip for a easy hand-taking
- Support 1D,2D barcode printing;
- While compatible with Windows, Linux, Android and IOS systems;
- Super battery life, with smart power saving and power consumption control functions , to ensure longer print time;
- Rich Interface optional: USB/USB+Bluetooth/USB+WiFi/USB+Bluetooth+WiFi;
- Support USB fast charging and realize printing while charging, which can greatly provide printing efficiency;
- Anti fall of 1.5M cement floor;

Application:

Warehousing, transportation, logistics, supermarket, tobacco, hydro-power reading, mobile government affairs, mobile police,postal and other industries

Parameters:

Item		Parameter
Print parameter	Printing Method	Thermal Line
	Effective Printing Width	48mm
	Resolution	384 dots/line (8dots/mm, 203dpi)
	Printing Speed	90 mm/S(MAX)
	Interface	USB/USB+Bluetooth/USB+WiFi/USB+Bluetooth+WiFi
	Line spacing	3.75mm (Can adjust line spacing by command)
	Line No.	Font A:32 character /Line Font B:42 character/Line
	Character Size	ANK character, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots)
Bar code character	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/ThaiVietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Bar code	1D.Bar code: UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/CODABAR/CODE93/CODE128 2D.Bar code: QRCODE
Graphics printing	Graphics printing	Supports bitmap download and print (support each bitmap size Max.8K, download up to 5pcs)
Power saving Mode	Smart power saving	Support
	Variable speed printing	Support
	Consumption	Support
	Dormancy	Support
Detection	Sensor	Lack of paper detection
Indicator	Power Display	Support
	Charge Indicator	Support
	Lack of paper	Support
Paper	Type	Thermal
	Width	57.5±0.5mm
	thickness	≤0.12mm
	Diameter	≤40mm
	Feed	Easy (Clamshell feed)
Print commands	Commands	ESC/POS
Power	Type	Rechargeable Lithium polymer battery
	Capacity	1500mAh/7.4V,
	Charger	5.0V/1A

Buffer	Input	4KB
	NV Flash	40KB
Physical features	Weight	200G
	Dimension	112*79*48(MM)
Environment	Operating	Temp: 5 ~ 45℃ , Humidity: 10 ~ 80%
	Storage	Temp: -10 ~ 50℃ , Humidity: 10 ~ 90% (No Dew)
Reliability	Print head life	50KM (Printing Density≤12.5)
Software	Driver	Android,IOS,Linux,Windows