

H58 Thermal Receipt Printer



Product Introduction:

HOP-H58 is a well-designed economic printer for common thermal bill printing ,this mold is with solid material,Exquisite workmanship.Transparent cover design, simple and fashion, easy for users to know the paper rolls' Using status,HOP-H58 adopt built-in power supply,not only can save space,but also easy for users to configure and use the printers.It's a very good choice for economical printing.

Product Features:

Simple and fashion,With solid material,exquisite workmanship.

Easy paper install structure,simple and convenient to operate

Built-in power supply design, to save space and more convenient to configure;

Transparent cover design, the user can know the paper roll's using status anytime;

Support GB18030 big font, easy to print uncommon characters

Support multi language print, suitable for users all over the world;

Support download and print LOGO&graphics ;

Support Windows, Linux, Android and IOS system printing

Application Area:

Shopping malls, restaurants, stores, warehousing, taxation, banking, medical, postal

Parameters:

Items		Parameters
Print parameters	Printing Method	Thermal Line
	Printing Method	48MM
	Resolution	384dots/Line (8dots/mm, 203dpi)
	Printing Speed	90mm/Second
	Interface Type	USB,USB+Bluetooth,USB+Wifi,Serial
	Line Spacing	3.75 mm (Can adjust line spacing by command)
	Line No.	Font A:32 character /Line Font B:42 character/Line Simple,traditional Chinese-16 lines
	Character	Standard GB18030 simplified / traditional Chinese Fonts
	Character Size	ANKcharacter, Font A: 1.5×3.0mm (12×24 点) Font B: 1.1×2.1mm (9×17 点) Simplified/Traditional Chinese: 3.0×3.0mm(24×24 Dots)
Bar code Character	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/Thai/Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Bar code	1D bar code: UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/CODABAR/CODE93/CODE128 2D bar code: QRCODE
Graphics printing	Graphics printing	Supports bitmap download and print
Paper	Type	Thermal Roll
	Width	57.5±0.5mm

	Diameter	≤60mm
	Feed Method	Easy feed(Clameshell feed)
Print commands	Commands	ESC/POS
Power	Power Adaptor	Input: AC 100V-240V,50-60Hz Output: DC 12V/2A
	Casher Drawer output	DC 12V/1A
Buffer	Input Buffer	4K
	NV Flash	40K
physical characteristics	Weight	590g
	Dimension	185*130*112(MM)
Environment	Working	Temp: 5 ~ 45℃ , Humidity: 10 ~ 80%
	Storage	Temp: -10 ~ 50℃ , Humidity: 10 ~ 90% (No dew)
Reliability parameter	Print Head Life	50KM (print density≤12.5)
	Cutter Life	500,000times